



1, RAHUL CHAMBERS, OPP.FORBES MARSHALL LTD., MUMBAI-PUNE ROAD, KASARWADI, PUNE - 411 034.

PHONE : (O) 2714 6183 /27147183 TELEFAX : (020) 2714 7183. Office Cell 9420045678 /9423508132

E-MAIL : sales@rajyogenterprises.com / rajyog_enterprises@vsnl.net / . WEBSITE :http://www.rajyogenterprises.com

Dealers in : Welding Electrodes, Arc and Gas welding Accessories and Safety equipments.

DESCRIPTION**Price + 18 %GST Extra*****Electrode & Flux Drying Ovens (AUTHORISED DEALER FOR HARIDAS OVENS)******506) Haridas make Portable Electrode Drying Ovens. (Leaflet With Price)***

Portable Electrode Drying Oven SPECIFICATION	1) HIEC 250 P** Precisely Powerful (With Thermostat Control)	2) HIEC 200 Simply Powerful	3) HIEC 200 ER Power -Conscious (With Engery Regulator)	4) HIEC 200 AC/DC Powerful Alternative (when there is noAC ***
Overall Size(mm)(Pkg)	665 x 200 x 275(HWD)	690 x 190 x 150(HWD)	690 x 190 x 275(HWD)	690 x 190 x 150(HWD)
Working Space (mm) (Dia. x Depth)	80mm x 445mm	62mm x 432mm	62mm x 432mm	62mm x 432mm
Capacity (approx)	4 Kg.	2 Kg.	2 Kg	2 Kg
Temperature Range.	Ambient - 250 ^o C	Ambient - 200 ^o C	Ambient - 200 ^o C	Ambient - 200 ^o C
Input Power.	500 Watts	165 Watts	165 Watts	75 Watts
Input current.	2 Amps.	0.7 Amps	0.7 Amps	1 Amps
Input Supply.	230/240 Volts AC, Single Phase , 50 HZ.	230/240 Volts AC, Single Phase , 50 HZ.	230/240 Volts AC, Single Phase , 50 HZ	80 Volts***
Air Circulation.	Natural convection	Natural convection	Natural convection	Natural convection
Type of Control.	Thermostatic (Range : 50 ^o C -300 ^o C)	-	Energy Regulator (Variable time delay control)	-
Weight.(Approx)	9Kg.	4 Kg.	4.5 Kg.	4 Kg.
Wooden Box Packing Extra (If Required)	Rs 400=00	Rs 400=00	Rs 400=00	Rs 400=00
Price (Rs.)	Rs. 3,822=00	Rs. 2,069 =00	Rs. 2,273=00	Rs. 2,336=00

Portable ovens can also be Supplied with 10 mtr. long 3-core cable with metal cladded Plug at an Extra Cost.

** HIEC 250 P can be supplied with 110 Volts AC

*** INPUT SUPPLY OF 80 Volts (Used with welding Machine Output Terminal and earthing)

Portable Electrode Drying Oven	5) HIEC 200 TSP Precisely Powerful (With Thermostat Control)	6) HIEC 250 H Portable Holding Oven	Mother Ovens (Cabinet Size) SPECIFICATION	7) HIEC 250 M Mini Mother Oven (Cabinet Size)
Overall Size(mm)(Pkg.)	690 x190x275 (HWD)		Overall Size(mm)(Pkg.)	685 x 455 x 625(HWD)
Working Space (mm)	62mm x 432mm	125x175x 450mm	Working Space (mm)	300 x300 x 480(HWD)
Capacity (approx)	2 Kg.	8 Kg.	Capacity (approx)	15 Kg.
Tempreture Range.	Ambient 200 ^o C	Ambient - 250 ^o C	No. of Shelves	Five
Input Power.	165 Watts	1 kW	Temperature Range.	50 ^o C - 250 ^o C
Input current	0.7 Amps.		Input Power.	1.5 kW
Input Supply.	230/240 Volts AC, Single Phase , 50 HZ	230/240 Volts AC, Single Phase , 50 HZ	Input current.	6.5 Amps
Air Circulation.	Natural convection	Natural convection	Input Supply.	230/240 Volts AC, Single Phase , 50 HZ
Type of Control.	Thermostatic (Range : 50 ^o C-300 ^o C)	Thermostatic (Range : 50 ^o C-300 ^o C)	Power Saving	
Weight.(Approx)	5 Kg.	17 Kg.	Air Circulation.	Through 3-Heat Switch Natural convection
Wooden Box Packing Extra (If Required)	Rs 400=00	Rs 400=00	Type of Control.	Thermostatic (Range : 50 ^o C -300 ^o C)
Price (Rs)	Rs. 3,124=00	Rs. 8,925=00	Weight.(Approx)	52 Kg.
			Wooden Box Packing Extra (If Required)	Rs. 1050=00
			Price (Rs) -	Rs. 12,002=00